

EARTHMAX SR 468



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 468

EARTHMAX SR 468 is an All Steel radial tyre specially designed for rigid haul trucks. Its unique tread design with special tread compounds makes it perfect for hard, rocky and tough mining conditions. Its tread lug blocks with circumferential grooves and intertwined blocks ensures effective heat dissipation. EARTHMAX SR 468 is developed using BKT's cutting-edge technology to carry heavy loads, deliver longer service life and provide resistance to rock cuts and punctures.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø49"	27.00 R 49	TL	E4	**	223 B	19.50/4.0	-	392	735	2720	1235	8351	83	CR
	27.00 R 49	TL	E4	***	226 B	19.50/4.0	-	505	735	2720	1235	8351	83	STD
	27.00 R 49	TL	E4	**	223 B	19.50/4.0	-	458	735	2720	1235	8351	83	STD
	27.00 R 49	TL	E4	***	226 B	19.50/4.0	-	432	735	2720	1235	8351	83	CR

CR: CUT RESISTANT COMPOUND, HRC: HEAT RESISTANT COMPOUND, STD: STANDARD, STANDARD : STANDARD

TECHNOLOGIES			PERFORMANCES		
					
					
B	257 kg				

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 06/10/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø51"	33.00 R 51	TL	E4	***	238 B	24.00/5.0	-	615	920	3080	1374	9323	94	CR
	NEW 33.00 R 51	TL	E4	**	235 B	24.00/5.0	-	651	920	3080	1374	9323	94	STANDARD
	NEW 33.00 R 51	TL	E4	***	238 B	24.00/5.0	-	715	920	3080	1374	9323	94	STD
Ø57"	50/80 R 57	TL	E4	**	257 B	32.00/6.0	29.00/6.0 34.00/6.0	950	1205	3610	1597	10870	96	CR
	40.00 R 57	TL	E4	**	250 B	29.00/6.0	32.00/6.0	800	1125	3575	1595	10700	100	CR
	37.00 R 57	TL	E4	***	249 B	27.00/6.0	29.00/6.0	1100	1030	3425	1520	10315	88	HRC
	37.00 R 57	TL	E4	**	245 B	27.00/6.0	29.00/6.0	850	1030	3425	1520	10315	88	STD
	46/90 R 57	TL	E4	**	252 B	29.00/6.0	32.00/6.0	1165	1140	3575	1590	10800	100	HRC
	37.00 R 57	TL	E4	**	245 B	27.00/6.0	29.00/6.0	725	1030	3425	1520	10315	88	CR

CR: CUT RESISTANT COMPOUND, HRC: HEAT RESISTANT COMPOUND, STD: STANDARD, STANDARD : STANDARD

TECHNOLOGIES			PERFORMANCES		
					
					
B	257 kg				

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baktishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 06/10/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (mm) 	OD (mm) 	SLR (mm) 	RC (mm) 	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
40.00 R 57	TL	E4	**	250 B	29.00/6.0	32.00/6.0	1130	1125	3575	1595	10700	100	HRC
50/80 R 57	TL	E4	**	257 B	32.00/6.0	29.00/6.0 34.00/6.0	1340	1205	3610	1597	10870	96	HRC
46/90 R 57	TL	E4	**	252 B	29.00/6.0	32.00/6.0	980	1140	3575	1590	10800	100	STD
46/90 R 57	TL	E4	**	252 B	29.00/6.0	32.00/6.0	825	1140	3575	1590	10800	100	CR
50/80 R57	TL	E4	**	257 B	32.00/6.0	29.00/6.0 34.00/6.0	1130	1205	3610	1597	10870	96	STD
40.00 R 57	TL	E4	**	250 B	29.00/6.0	32.00/6.0	950	1125	3575	1595	10700	100	STD
37.00 R 57	TL	E4	**	245 B	27.00/6.0	29.00/6.0	1020	1030	3425	1520	10315	88	HRC
37.00 R 57	TL	E4	***	249 B	27.00/6.0	29.00/6.0	962	1030	3425	1520	10315	88	STD

CR: CUT RESISTANT COMPOUND, HRC: HEAT RESISTANT COMPOUND, STD: STANDARD, STANDARD : STANDARD

TECHNOLOGIES			PERFORMANCES		
					
					
B	E4	257 kg			

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 06/10/2026



TECHNOLOGIES		PERFORMANCES
  E4		   
 B	 257 kg	

Permissible tolerances: O.D. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 06/10/2026