


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>520/85 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94040834	<b>RC (IN)</b>	230.9
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	78.3	<b>RIM ALT</b>	DD 18 L ; DW 18 L
<b>SLR (IN)</b>	35.6	<b>ECE</b>	E4-106R-000793

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	5000	5820	6650	7460	8280	9100
25	5000	5820	6650	7460	8280	9100
20	5360	6240	7110	7990	8860	9730
5 LT	6710	7800	8910	10000	11100	12190
5 HT	5360	6240	7110	7990	8860	9730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.