


EARTHMAX SR 49 M



| | |
|---------------------|--|
| TIRE SIZE | 29.5 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | DOZER / PALA LHD / PALA CARICATRICE / DUMPER DI BASSO PROFILO |
| VERSIONE | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 200 B ; 216 A2 |

DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|--------------------|-----------|
| CODICE USA | 94516766 | RIM REC | 25.00/3.5 |
| OD (IN) | 75.0 | TRA CODE | E4/L4 |
| SLR (IN) | 33.2 | STAR RATING | ★★ |
| RC (IN) | 220.5 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58 | 62 | 65 | 69 | 73 | 76 | 80 | 83 | 87 | 91 | 94 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 25400 | 26000 | 27600 | 28300 | 30000 | 30900 | - | - | - | - | - |
| 5 | - | - | - | - | - | 41900 | 43000 | 44100 | 45400 | 46700 | 49400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.