

# EARTHMAX SR 43

|                     |                        |
|---------------------|------------------------|
| <b>TIRE SIZE</b>    | <b>875/65 R 29</b>     |
| <b>UM</b>           | US STANDARD            |
| <b>CONSTRUCTION</b> |                        |
| <b>MACHINERY</b>    | LOADER                 |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND |
| <b>TIRE TYPE</b>    | TL                     |
| <b>LI/SS</b>        | 228 A2                 |



## DIMENSIONS US STANDARD

|                 |          |                    |                      |
|-----------------|----------|--------------------|----------------------|
| <b>USA CODE</b> | 94071098 | <b>RIM REC</b>     | 27.00/3.5            |
| <b>OD (IN)</b>  | 73.9     | <b>RIM ALT</b>     | 27.00/3.0; 28.00/3.5 |
| <b>SLR (IN)</b> | 33.2     | <b>TRA CODE</b>    | L4                   |
| <b>RC (IN)</b>  | 224.5    | <b>STAR RATING</b> | ★★★                  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 94    | 98    | 102   | 105   | 109   | 112   | 116   |
|-----------|-------|-------|-------|-------|-------|-------|-------|
| 5         | 58400 | 60000 | 61500 | 64000 | 66000 | 68000 | 69500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.