


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>650/75 R 32 CHO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / COTTON PICKER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	172 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	670	<b>RIM REC</b>	DW 21 B
<b>OD (MM)</b>	1795	<b>RIM ALT</b>	DW 20 B; DW 23 B
<b>SLR (MM)</b>	816	<b>ECE</b>	E4-106R-001425
<b>RC (MM)</b>	5378	<b>SRI</b>	850

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
<b>50</b>	2900	3340	4095	4475	4915	5355	5800	6300
<b>40</b>	2900	3340	4095	4475	4915	5355	5800	6300
<b>30</b>	3105	3575	4385	4790	5265	5735	6210	6745
<b>15 CYC</b>	4785	5510	6760	7385	8110	8840	9565	10395
<b>10 CYC</b>	5220	6015	7375	8055	8850	9640	10435	11340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.