


# AW 702

<b>TIRE SIZE</b>	<b>10.5/80 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / REMORCĂ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	138 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94009343	<b>RC (IN)</b>	102.1
<b>SW (IN)</b>	10.8	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	34.8	<b>RIM ALT</b>	W 8; 9
<b>SLR (IN)</b>	15.6	<b>ECE</b>	E11-106R-003577

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	74
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.