

# FLOTATION 648

<b>TIRE SIZE</b>	<b>850/50 - 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	168 A8/164 B
<b>LI/SS FREE ROLLING</b>	180 A8/176 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94006571	<b>RC (IN)</b>	194.3
<b>SW (IN)</b>	33.5	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	65.0	<b>ECE</b>	E11-106R-004564
<b>SLR (IN)</b>	28.0	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	16	19	22
<b>5 FR</b>	20600	22720	24690
<b>10 FR</b>	18540	20450	22220
<b>20 FR</b>	16480	18180	19750
<b>25 FR</b>	14720	16230	17640
<b>30 FR</b>	13250	14600	15650
<b>5 DW</b>	14420	15890	17280
<b>10 DW</b>	12970	14310	15550
<b>20 DW</b>	11530	12720	13820
<b>25 DW</b>	10300	11350	12350
<b>30 DW</b>	9270	10220	11020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.