


# PL 801

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>8.25 - 15</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS                               |
| <b>MACHINERY</b>    | ADAINEUR ROTATIF / MOISSONNEUSE<br>/ CHARIOT ÉLÉVATEUR /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE / CHARIOT ÉLÉVATEUR |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>CODE USA</b> | 94007301 | <b>RIM ALT</b> | 6.0; 7.0        |
| <b>SW (IN)</b>  | 9.3      | <b>ECE</b>     | E11-106R-003402 |
| <b>OD (IN)</b>  | 33.6     | <b>PR</b>      | 14              |
| <b>RIM REC</b>  | 6.5      |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI                 | 116   |
|---------------------------|-------|
| <b>15 LOAD WHEEL</b>      | 9315  |
| <b>15 STEER WHEEL</b>     | 7165  |
| <b>5 OTHER VEHICLES</b>   | 9315  |
| <b>15 OTHER VEHICLES</b>  | 7165  |
| <b>STATIC SIDE LOADER</b> | 10825 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.