DATA SHEET

PRINTED ON
23-04-2026

RIDEMAX FL 690

TIRE SIZE	**30.5L R 32**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA / REMOLQUE
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	184 A8 ; 181 B

DIMENSIONES IS STANDARD

SW (MM)	790	**RIM REC**	DH 27 B
OD (MM)	1800	**RIM ALT**	DW 27 B
SLR (MM)	806	**ECE**	E11-106R-002986
RC (MM)	5430	**SRI**	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.0
50	3795	4375	5280	5695	6520	7260	7920	8250
40	4370	5030	6075	6550	7500	8355	9115	9490
30	4935	5685	6865	7405	8475	9440	10300	10725
25	5205	5995	7240	7805	8935	9950	10855	11305
10	6040	6955	8400	9055	10365	11550	12600	13120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..