

# AS 504

<b>TIRE SIZE</b>	<b>16.0/70 - 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	144 A8
<b>LI/SS FREE ROLLING</b>	156 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94032808	<b>RC (IN)</b>	126.5
<b>SW (IN)</b>	16.5	<b>RIM REC</b>	13
<b>OD (IN)</b>	43.2	<b>RIM ALT</b>	12 SDC; 14; 13 SDC
<b>SLR (IN)</b>	19.2	<b>ECE</b>	E11-106R-004611

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58
5 FR	12350
15 FR	10490
20 FR	9880
25 FR	8820
5 DW	8640
15 DW	7340
20 DW	6910
25 DW	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.