

AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 250/85 R 20 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 116 A8/B |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94027460 | RC (IN) | 110.7 |
| SW (IN) | 9.8 | RIM REC | W 8 |
| OD (IN) | 37.0 | RIM ALT | W 7 ; W 9 |
| SLR (IN) | 16.7 | ECE | E4-106R-000639 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-------------|------|------|------|------|------|------|------|------|
| 30 | 1300 | 1490 | 1710 | 1930 | 2150 | 2370 | 2570 | 2760 |
| 25 | 1300 | 1490 | 1710 | 1930 | 2150 | 2370 | 2570 | 2760 |
| 20 | 1390 | 1600 | 1840 | 2070 | 2310 | 2550 | 2760 | 2950 |
| 5 LT | 1740 | 2000 | 2290 | 2590 | 2890 | 3190 | 3440 | 3690 |
| 5 HT | 1390 | 1600 | 1840 | 2070 | 2310 | 2550 | 2760 | 2950 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.