

AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 5.00 - 15 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 67 A8 |
| LI/SS FREE ROLLING | 79 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|---------------------|
| SW (MM) | 140 | RIM REC | 3.50 D |
| OD (MM) | 657 | RIM ALT | 3.00 D; 4.00 E; 4 J |
| SLR (MM) | 308 | ECE | E11-106R-004237 |
| RC (MM) | 1957 | PR | 4 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.30 |
|------------|------|
| 10 FR | 610 |
| 25 FR | 520 |
| 30 FR | 485 |
| 40 FR | 435 |
| 10 DW | 425 |
| 25 DW | 365 |
| 30 DW | 340 |
| 40 DW | 305 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.