


# FLOTATION 648

<b>TIRE SIZE</b>	<b>500/50 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	140 A8/136 B
<b>LI/SS FREE ROLLING</b>	152 A8/148 B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94027798	<b>RC (IN)</b>	126.0
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	42.1	<b>PR</b>	12
<b>SLR (IN)</b>	18.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	29	32
<b>5 FR</b>	8750	10350	10960
<b>10 FR</b>	7870	9310	9870
<b>20 FR</b>	7000	8290	8760
<b>25 FR</b>	6250	7400	7830
<b>30 FR</b>	5620	6660	6940
<b>5 DW</b>	6170	7300	7720
<b>10 DW</b>	5560	6570	6940
<b>20 DW</b>	4940	5840	6170
<b>25 DW</b>	4410	5210	5510
<b>30 DW</b>	3970	4700	4940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.