


AGRIMAX V-FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 710/60 R 30 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTEUR DE FORTE PUISSANCE / TRACTEUR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 171 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| CODE USA | 94513505 | RC (IN) | 189.0 |
| SW (IN) | 28.3 | RIM REC | DW 25 B |
| OD (IN) | 64.0 | RIM ALT | DW 24 B; DW 27 B |
| SLR (IN) | 27.6 | ECE | E11-106R-0010832 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 |
|--------------------------------------|------|-------|-------|-------|-------|-------|-------|
| 45 | 6040 | 7020 | 8130 | 9130 | 10110 | 11100 | 12330 |
| FROM 40 TO 25 | 6640 | 7730 | 8940 | 10030 | 11110 | 12200 | 13560 |
| 20 | 6770 | 7870 | 9120 | 10220 | 11330 | 12430 | 13820 |
| 12 | 6900 | 8040 | 9300 | 10430 | 11550 | 12690 | 14100 |
| 5 | 7300 | 8500 | 9830 | 11030 | 12220 | 13410 | 14910 |
| *UPTO 5 CYC WITH FRONT LOADER | 9290 | 10810 | 12520 | 14040 | 15560 | 17070 | 18980 |
| 5 HT | 6770 | 7870 | 9120 | 10220 | 11330 | 12430 | 13820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.