


# AGRIMAX V-FLECTO



TIRE SIZE	VF 710/55 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	175 D

## DIMENSIONS IS STANDARD

SW (MM)	710	RIM REC	DW 25 B
OD (MM)	1750	RIM ALT	DW 24 B
SLR (MM)	780	ECE	E11-106R-006844
RC (MM)	5242	SRI	825

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2890	3330	3830	4270	4770	5210	5840	6275
FROM 65 TO 40	3175	3660	4210	4695	5245	5730	6420	6900
30	3240	3730	4295	4785	5350	5840	6545	7035
20	3305	3805	4380	4880	5455	5960	6675	7175
10	3495	4025	4630	5165	5770	6300	7060	7590
*UPTO 10 CYC WITH FRONT LOADER	4445	5120	5895	6570	7345	8020	8985	9660
10HT	3240	3730	4295	4785	5350	5840	6545	7035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.