


# EARTHMAX SR 459

|              |  |
|--------------|--|
| TIRE SIZE    | 27.00 R 49   |
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | DÚMPER RIGIDO  |
| VERSIÓN      | CUT RESISTANT COMPOUND   |
| TIRE TYPE    | TL   |
| LI/SS        | 223 B  |



## DIMENSIONES US STANDARD

|            |          |             |           |
|------------|----------|-------------|-----------|
| CÓDIGO USA | 94512591 | RIM REC     | 19.50/4.0 |
| OD (IN)    | 107.1    | TRA CODE    | E4        |
| SLR (IN)   | 48.5     | STAR RATING | ★★        |
| RC (IN)    | 324.6    |             |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 45400 | 48100 | 49400 | 50700 | 52000 | 55100 | 56800 | 58400 | 60000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.