


AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 230/95 R 48 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPRAYER / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 136 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 228 | RIM REC | W 7 |
| OD (MM) | 1656 | RIM ALT | W 8 |
| SLR (MM) | 792 | ECE | E4-106R-000778 |
| RC (MM) | 5085 | SRI | 800 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 875 | 1145 | 1390 | 1525 | 1615 | 1770 | 1930 | 2085 | 2240 | - |
| 40 | 875 | 1145 | 1390 | 1525 | 1615 | 1770 | 1930 | 2085 | 2240 | - |
| 30 | 940 | 1225 | 1490 | 1635 | 1730 | 1900 | 2065 | 2235 | 2400 | - |
| 10 | 1045 | 1315 | 1615 | 1920 | 2220 | 2285 | 2555 | 2825 | 3095 | 3360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.