


EARTHMAX SR 22 AS

TIRE SIZE	23.5 R 25
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ПОГРУЗЧИК / ГРЕЙДЕР
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	185 B ; 170 A8 ; 201 A2



РАЗМЕРЫ US STANDARD

USA CODE	94073405	RIM REC	19.50/2.5
OD (IN)	63.5	TRA CODE	E2/G2/L2
SLR (IN)	27.9	STAR RATING	★★/★/★★
RC (IN)	191.5		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91
30	-	-	-	-	-	-	-	-	16500	17100	18200	18700	19800	20400	-	-	-	-
25	6950	7850	8800	9900	10700	11700	12300	13200	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	27600	28300	29100	30000	30900
MPH / PSI	94																	
30	-																	
25	-																	
5	32000																	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.