


AGRIMAX V- FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 710/75 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR DE ALTA POTENCIA / TRACTOR |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 183 D |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 720 | RIM REC | DW 24 B |
| OD (MM) | 2060 | RIM ALT | DW 23 B; DW 25 B |
| SLR (MM) | 905 | ECE | E11-106R-006764 |
| RC (MM) | 6151 | SRI | 950 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 |
|--------------------------------|------|------|------|------|-------|-------|-------|
| 70 | 3980 | 4615 | 5255 | 5965 | 6605 | 7240 | 7960 |
| FROM 65 TO 40 | 4375 | 5075 | 5775 | 6560 | 7260 | 7960 | 8750 |
| 30 | 4460 | 5175 | 5890 | 6690 | 7405 | 8115 | 8925 |
| 20 | 4550 | 5275 | 6005 | 6820 | 7550 | 8275 | 9100 |
| 10 | 4810 | 5580 | 6350 | 7215 | 7985 | 8755 | 9625 |
| *UPTO 10 CYC WITH FRONT LOADER | 6125 | 7105 | 8085 | 9180 | 10160 | 11140 | 12250 |
| 10 HT | 4460 | 5175 | 5890 | 6690 | 7405 | 8115 | 8925 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.