


AGRIMAX RT 657

| | |
|---------------------|--|
| | 320/65 R 16 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 117 D ; 120 A8 |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94042036 | RC (IN) | 97.1 |
| SW (IN) | 12.6 | RIM REC | W 10 |
| OD (IN) | 32.4 | RIM ALT | W 9 ; W 11 |
| SLR (IN) | 14.4 | ECE | E4-106R-001815 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|------|
| 40 | 1330 | 1570 | 1790 | 1980 | 2180 | 2360 | 2610 | 2830 |
| 30 | 1400 | 1640 | 1880 | 2080 | 2290 | 2480 | 2740 | 2980 |
| 25 | 1450 | 1700 | 1950 | 2160 | 2380 | 2570 | 2840 | 3090 |
| 20 | 1540 | 1800 | 2060 | 2290 | 2510 | 2710 | 3010 | 3260 |
| 5 LT | 1800 | 2090 | 2400 | 2670 | 2930 | 3160 | 3510 | 3800 |
| 5 HT | 1540 | 1800 | 2060 | 2290 | 2510 | 2710 | 3010 | 3260 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.