

AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 16.5/85 - 24 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 155 A8 |
| LI/SS FREE ROLLING | 168 A8 |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 415 | RIM REC | W 13 |
| OD (MM) | 1325 | RIM ALT | W 14 L; W 15 L |
| SLR (MM) | 584 | ECE | E4-106R-001877 |
| RC (MM) | 4013 | PR | 16 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.80 |
|------------|-------------|
| 10 FR | 7840 |
| 25 FR | 6665 |
| 30 FR | 6270 |
| 40 FR | 5600 |
| 10 DW | 5425 |
| 25 DW | 4610 |
| 30 DW | 4340 |
| 40 DW | 3875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.