

SKID POWER SK



SKID POWER SK



SKID POWER SK has been specially designed for skid steers in construction applications. Its sidewall and rim guard protectors as well as its deep tread provide an extended tire life-cycle.



SIZE	TT/TL	PR	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION	
				REC RIM	ALT RIM						
											
Ø16.5"	10 - 16.5	TL	8	116 A8	8.25	-		30.5	14.0	90.0	IMP
	12 - 16.5	TL	10	-	9.75	-		32.5	14.8	95.8	STD
	12 - 16.5	TL	12	-	9.75	-		32.5	14.8	95.8	STD
	12 - 16.5	TL	10	125 A8	9.75	-		32.5	14.8	95.8	IMP
	10 - 16.5	TL	12	138 A2	8.25	-		30.5	14.0	90.0	STD

IMP: IMPLEMENT, STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
A8	138 lbs		

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	TT/TL	PR	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
				REC RIM	ALT RIM					
										
10 - 16.5	TL	10	120 A8	8.25	-		30.5	14.0	90.0	IMP
12 - 16.5	TL	12	130 A8	9.75	-		32.5	14.8	95.8	IMP
10 - 16.5	TL	8	-	8.25	-		30.5	14.0	90.0	STD
10 - 16.5	TL	10	-	8.25	-		30.5	14.0	90.0	STD

IMP: IMPLEMENT, STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
  A8 138 lbs			Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026