


# FARM SPECIAL

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>12.4 - 24</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 118 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94060696 | <b>RC (IN)</b> | 138.0           |
| <b>SW (IN)</b>  | 12.6     | <b>RIM REC</b> | W 11            |
| <b>OD (IN)</b>  | 45.5     | <b>RIM ALT</b> | W 9; W 10       |
| <b>SLR (IN)</b> | 21.0     | <b>ECE</b>     | E11-106R-005529 |

## LOAD CAPACITY (LBS/TYRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>32</b> |
| 25               | 2830      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.