

AGRIMAX RT 657

TIRE SIZE	600/65 R 30
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	VENDEMMIATRICE / TRATTORE / MIETITREBBIA
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	155 D ; 158 A8



DIMENSIONI IS STANDARD

SW (MM)	611	RIM REC	DW 20 B
OD (MM)	1542	RIM ALT	W 18 L
SLR (MM)	697	ECE	E4-106R-001825
RC (MM)	4609	SRI	725

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1860	2170	2445	2715	2985	3220	3565	3875
50	1955	2280	2565	2850	3135	3380	3745	4070
40	2040	2380	2680	2975	3275	3530	3910	4250
30	2145	2500	2810	3125	3435	3705	4105	4460
10 LT	2495	2910	3275	3640	4005	4315	4780	5195
10 HT	2145	2500	2810	3125	3435	3705	4105	4460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.