DATA SHEET

PRINTED ON
23-04-2026

AGRIMAX TURF RT 333

TIRE SIZE	**240/70 R 16**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRAUBENERNTEMASCHINE / ERNTEMASCHINE FÜR OBST / KLEINTRAKTOR / TRACTOR / ERNTEMASCHINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	104 A8/B

ABMESSUNGEN US STANDARD

USA-CODE	94070282	**RC (IN)**	87.1
SW (IN)	9.6	**RIM REC**	W8
OD (IN)	29.2	**RIM ALT**	W 8 L; W 9
SLR (IN)	13.4	**ECE**	E11-106R-007531

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	940	1090	1240	1390	1560	1710	1880	1990
25	940	1090	1240	1390	1560	1710	1880	1990
20	1010	1160	1330	1500	1670	1830	2010	2130
5 LT	1260	1450	1670	1880	2090	2310	2520	2670
5 HT	1010	1160	1330	1500	1670	1830	2010	2130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..