

AGRIMAX RT 657

TIRE SIZE	320/65 R 16
UM	IS STANDARD
MACHINERY	VINEYARD HARVESTER / TRACTOR / HARVESTER
VERSION	STANDARD
TL/TT	TL
LI/SS	117 D ; 120 A8



DIMENSIONS IS STANDARD

SW (MM)	319	ECE	E4-106R-001815
OD (MM)	822	SRI	390
SLR (MM)	366	TRA CODE	R1W
RC (MM)	2466	TREAD DEPTH (MM)	32,5
RIM REC	W 10	TKPH (TK/H)	0
RIM ALT	W 9 ; W 11		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	605	710	810	900	990	1070	1185	1285
50	635	745	855	945	1040	1125	1245	1350
40	660	770	885	980	1080	1165	1290	1400
30	700	815	935	1040	1140	1230	1365	1480
10 LT	815	950	1090	1210	1330	1435	1590	1725
10 HT	700	815	935	1040	1140	1230	1365	1480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.