


# AT 603

**12.5/80 - 18**

|                     |  |
|---------------------|--|
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | UYGULAMALI MAKINE / BEKOLODER /<br>UYGULAMALI MAKINE / BEKOLODER                       |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 135 A8   |
|                     | 148 A8   |



## UNDEFINED US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94019663 | <b>RC (IN)</b> | 119.2           |
| <b>SW (IN)</b>  | 12.1     | <b>RIM REC</b> | W 9             |
| <b>OD (IN)</b>  | 39.4     | <b>RIM ALT</b> | 11              |
| <b>SLR (IN)</b> | 17.6     | <b>ECE</b>     | E11-106R-004351 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 71   |
|-----------|------|
| 5 FR      | 9720 |
| 15 FR     | 8270 |
| 20 FR     | 7780 |
| 25 FR     | 6940 |
| 5 DW      | 6720 |
| 15 DW     | 5720 |
| 20 DW     | 5380 |
| 25 DW     | 4810 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.