

TR 882

TIRE SIZE	400/60 - 15.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019908	RC (IN)	102.6
SW (IN)	15.7	RIM REC	AG 13.00
OD (IN)	34.4	ECE	E4-106R-001878
SLR (IN)	14.9	PR	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160
5 DW	7100
15 DW	6030
20 DW	5680
25 DW	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.