


AW 711

| | |
|---------------------|--|
| TIRE SIZE | 340/60 R 16.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SKÖRDEMASKIN / ARBETSFORDON / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STUBBLE RESISTANT |
| TIRE TYPE | TL |
| LI/SS | 145 A8/B |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 324 | RIM REC | 11 |
| OD (MM) | 820 | ECE | E4-106R-001392 |
| SLR (MM) | 368 | SRI | 390 |
| RC (MM) | 2476 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 870 | 1135 | 1395 | 1595 | 1860 | 2120 | 2265 | 2495 | 2730 | 2900 |
| 40 | 870 | 1135 | 1395 | 1595 | 1860 | 2120 | 2265 | 2495 | 2730 | 2900 |
| 30 | 975 | 1270 | 1560 | 1790 | 2080 | 2375 | 2535 | 2795 | 3055 | 3250 |
| 25 | 1040 | 1350 | 1660 | 1905 | 2215 | 2525 | 2695 | 2975 | 3250 | 3455 |
| 20 | 1100 | 1430 | 1755 | 2015 | 2340 | 2670 | 2855 | 3145 | 3440 | 3655 |
| 10 | 1220 | 1585 | 1950 | 2235 | 2600 | 2965 | 3170 | 3495 | 3820 | 4060 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.