


FL 630 ULTRA

| | |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE | 710/50 R 26.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | YAYICI / TANKER / RÖMORK / UYGULAMALI MAKINE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 170 D ; 181 A8 |



BOYUTLAR US STANDARD

| | | | |
|----------|----------|---------|-----------------|
| USA CODE | 94047284 | RC (IN) | 165.7 |
| SW (IN) | 28.6 | RIM REC | AG 24.00 |
| OD (IN) | 54.4 | RIM ALT | AG 20.00 |
| SLR (IN) | 23.6 | ECE | E11-106R-006812 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 3860 | 4400 | 4940 | 6140 | 6990 | 8070 | 9150 | 10000 | 10960 | 12040 |
| 40 | 4230 | 4830 | 5420 | 6750 | 7670 | 8860 | 10050 | 10980 | 12040 | 13230 |
| 30 | 5130 | 5850 | 6570 | 8170 | 9290 | 10720 | 12170 | 13290 | 14570 | 16000 |
| 25 | 5820 | 6650 | 7460 | 9280 | 10550 | 12190 | 13820 | 15100 | 16560 | 18190 |
| 15 | 6690 | 7640 | 8580 | 10660 | 12120 | 14010 | 15880 | 17350 | 19020 | 20900 |
| 5 | 7630 | 8700 | 9700 | 12150 | 13810 | 15960 | 18100 | 19760 | 21670 | 23810 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.