DATA SHEET

PRINTED ON
23-04-2026

FLOTATION 648

TIRE SIZE	**385/65 - 22.5**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	148 A8/144 B
LI/SS FREE ROLLING	160 A8/ 156 B

DIMENSIONES US STANDARD

CÓDIGO USA	94006298	**RC (IN)**	127.3
SW (IN)	15.7	**RIM REC**	AG 11.75
OD (IN)	42.1	**ECE**	E4-106R-002263
SLR (IN)	18.7	**PR**	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	55	58	62
5 FR	12920	13320	13890
10 FR	11630	11980	12500
20 FR	10330	10660	11110
25 FR	9230	9510	9920
30 FR	8300	8560	8820
5 DW	9040	9330	9720
10 DW	8130	8390	8750
20 DW	7230	7450	7780
25 DW	6460	6660	6940
30 DW	5810	6000	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..