



IS standard



GROWING TOGETHER

V-FLEXA



PRODUCT DATA SHEET



Radial



191



V-FLEXA

V-FLEXA is a radial tire specifically designed for agricultural trailers. It is a latest-generation flotation product featuring VF technology, which enables the transport of heavy loads both in the fields and on the road with an inflation pressure that is 30% less than that of a standard tire of the same size. Additional steel belts confer major resistance to the casing against impacts. Not only does V-FLEXA support heavy loads in full safety, it also avoids soil compaction thanks to perfect weight distribution. Moreover, V-FLEXA features great self-cleaning properties, durability as well as low rolling resistance.

Technologies



VF Technology



High Speed



Reinforced Bead



Extra Steel Belted

Performance



Reduced Soil Compaction



Traction



High Load Capacity



Durability



Low Rolling Resistance

	Tire size	LI/SS		RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version	
		DW	FR	Rec.	Alt.							
Ø 22.5"	VF 560/60 R 22.5	166 D		AG 16.00	-	555	1250	550	3756	600	SB	
	Ø 26.5"	VF 600/55 R 26.5	167 D		AG 20.00	-	615	1342	580	3986	650	SB
		VF 600/65 R 26.5	172 D		AG 20.00	-	615	1453	628	4377	700	SB
		VF 650/55 R 26.5	171 D		AG 20.00	-	644	1389	591	4100	650	SB
		VF 710/50 R 26.5	176 D	176 D	AG 24.00	-	727	1383	600	4193	650	SB
		VF 750/45 R 26.5	176 D	176 D	AG 24.00	-	755	1349	585	4095	650	SB
		VF 800/45 R 26.5	179 D	179 D	AG 28.00	AG 24.00	805	1393	602	4213	675	SB
Ø 30.5"	VF 710/50 R 30.5	178 D	178 D	AG 24.00	-	727	1485	654	4511	700	SB	
	VF 750/60 R 30.5	187 D	187 D	AG 24.00	-	780	1678	728	5085	800	SB	
	VF 750/60 R 30.5	187 D	187 D	AG 24.00	-	780	1678	728	5085	800	SB	
Ø 32"	VF 800/60 R 32 VF 30.5 L R 32	191 D	191 D	DW 27 B	DW 25 B	818	1799	785	5459	850	SB	

SB: Steel Belted

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index; DW = Drive Wheel; FR = Free Rolling