


AW 909

| | |
|---------------------------|---|
| TIRE SIZE | 10.0/80 - 12 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 116 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 264 | RIM REC | 9.00 |
| OD (MM) | 710 | RIM ALT | 7.0 |
| SLR (MM) | 313 | ECE | E4-106R-002663 |
| RC (MM) | 2080 | PR | 8 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.10 |
|------------|------|
| 10 FR | 1750 |
| 25 FR | 1490 |
| 30 FR | 1400 |
| 40 FR | 1250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.