


FLOTATION 648

TIRE SIZE	700/50 - 26.5
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	157 A8/154 B
LI/SS FREE ROLLING	169 A8/165 B



DIMENSIONES US STANDARD

CÓDIGO USA	94006519	RC (IN)	161.4
SW (IN)	27.6	RIM REC	24.00
OD (IN)	54.1	ECE	E4-106R-002278
SLR (IN)	24.4	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	23	26
5 FR	16090	16710	17900
10 FR	14480	15050	16110
20 FR	12870	13370	14320
25 FR	11500	11940	12790
30 FR	10350	10750	11350
5 DW	11450	11880	12730
10 DW	10310	10690	11460
20 DW	9160	9500	10180
25 DW	8180	8490	9090
30 DW	7360	7640	8270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.