


# AGRIMAX SPARGO

TIRE SIZE	VF 320/90 R 50
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	169 D



## DIMENSIONES IS STANDARD

SW (MM)	323	RIM REC	W 11
OD (MM)	1846	RIM ALT	W 10; DW 10; W 10 L; DW 11
SLR (MM)	865	ECE	E11-106R-007204
RC (MM)	5650	SRI	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4	4.8
70	2415	2685	2955	3085	3220	3330	3435	3595	3760	3810	3865	4105	4350	4455	4565	4775	4990	5365
FROM 65 TO 40	2610	2900	3190	3335	3480	3600	3715	3890	4060	4120	4180	4440	4700	4815	4930	5165	5395	5800
30	2665	2960	3260	3405	3555	3675	3790	3970	4145	4205	4265	4530	4800	4915	5035	5270	5510	5920
20	2720	3020	3320	3475	3625	3745	3865	4045	4225	4285	4350	4620	4890	5010	5130	5375	5615	6035
10	2875	3190	3510	3670	3830	3960	4085	4275	4470	4530	4595	4885	5170	5300	5425	5680	5935	6380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.