


# EARTHMAX SR 49 M

<b>TIRE SIZE</b>	<b>29.5 R 25</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	БУЛЬДОЗЕР / ПОГРУЗОЧНО-ДОСТАВОЧНАЯ МАШИНА / ПОГРУЗЧИК / НИЗКОПРОФИЛЬНЫЙ САМОСВАЛ
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	200 B ; 208 A2



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94058426	<b>RIM REC</b>	25.00/3.5
<b>OD (IN)</b>	75.0	<b>TRA CODE</b>	E4/L4
<b>SLR (IN)</b>	33.2	<b>STAR RATING</b>	★★/★
<b>RC (IN)</b>	220.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	--

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.