

# AGRIMAX RT 855

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 280/85 R 28                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA          |
| VERSIÓN      | SPECIAL                                                                                  |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 118 A8/B                                                                                 |



## DIMENSIONES IS STANDARD

|          |      |         |                |
|----------|------|---------|----------------|
| SW (MM)  | 292  | RIM REC | W 10           |
| OD (MM)  | 1187 | RIM ALT | W 9            |
| SLR (MM) | 545  | ECE     | E4-106R-000614 |
| RC (MM)  | 3558 | SRI     | 575            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|-----|------|------|------|------|------|
| 50         | 730 | 845  | 965  | 1085 | 1205 | 1320 |
| 40         | 730 | 845  | 965  | 1085 | 1205 | 1320 |
| 30         | 780 | 910  | 1035 | 1165 | 1290 | 1415 |
| 10 LT      | 975 | 1135 | 1295 | 1455 | 1615 | 1770 |
| 10 HT      | 780 | 910  | 1035 | 1165 | 1290 | 1415 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.