

# MP 600

<b>TIRE SIZE</b>	<b>400/70 - 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO / VEICULO UNIVERSAL
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	158 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94049318	<b>RC (IN)</b>	139.0
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	13 SDC
<b>OD (IN)</b>	46.7	<b>RIM ALT</b>	12
<b>SLR (IN)</b>	21.5	<b>ECE</b>	E11-106R-003641

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>65</b>
<b>25 DW</b>	9370
<b>30 DW</b>	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.