


# AGRIMAX RT 945

<b>TIRE SIZE</b>	<b>320/90 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	146 A8/B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	319	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	1744	<b>RIM ALT</b>	W 9 ; W 11
<b>SLR (MM)</b>	810	<b>ECE</b>	E4-106R-001399
<b>RC (MM)</b>	5232	<b>SRI</b>	825

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	1380	1770	2160	2370	2550	2790	3000	-
40	1380	1770	2160	2370	2550	2790	3000	-
30	1480	1895	2315	2540	2730	2990	3210	-
10	1620	2115	2565	3060	3510	3645	4050	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.