

# FLOTATION 648

<b>TIRE SIZE</b>	<b>550/45 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	147 A8/144 B
<b>LI/SS FREE ROLLING</b>	159 A8/156 B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	525	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1070	<b>ECE</b>	E4-106R-002309
<b>SLR (MM)</b>	488	<b>PR</b>	16
<b>RC (MM)</b>	3253		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.40	2.60	2.80
10 FR	5600	5865	6125
20 FR	5040	5280	5515
30 FR	4480	4695	4900
40 FR	4000	4190	4375
50 FR	3600	3770	4000
10 DW	3935	4125	4305
20 DW	3540	3710	3875
30 DW	3145	3300	3445
40 DW	2810	2945	3075
50 DW	2530	2650	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.