


# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 250/85 R 22  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS                    |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 113 A8/B   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 251  | <b>RIM REC</b> | W 8             |
| <b>OD (MM)</b>  | 985  | <b>RIM ALT</b> | W 7             |
| <b>SLR (MM)</b> | 453  | <b>ECE</b>     | E11-106R-002973 |
| <b>RC (MM)</b>  | 2964 | <b>SRI</b>     | 475             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|-----|-----|-----|------|------|------|------|------|
| 50         | 545 | 625 | 715 | 805  | 900  | 990  | 1070 | 1150 |
| 40         | 545 | 625 | 715 | 805  | 900  | 990  | 1070 | 1150 |
| 30         | 585 | 670 | 770 | 865  | 965  | 1065 | 1150 | 1235 |
| 10 LT      | 730 | 835 | 960 | 1085 | 1210 | 1330 | 1440 | 1545 |
| 10 HT      | 585 | 670 | 770 | 865  | 965  | 1065 | 1150 | 1235 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.