

AGRIMAX RT 855

TIRE SIZE	420/85 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	147 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94058532	RC (IN)	188.3
SW (IN)	17.2	RIM REC	W 15 L
OD (IN)	62.1	RIM ALT	W 13; W 14 L
SLR (IN)	28.7	ECE	E11-106R-005179

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	3200	3670	4210	4750	5290	5830	6380	6780
25	3200	3670	4210	4750	5290	5830	6380	6780
20	3420	3920	4510	5090	5680	6250	6830	7260
5 LT	4280	4920	5640	6370	7100	7830	8550	9090
5 HT	3420	3920	4510	5090	5680	6250	6830	7260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.