


# RT 853

<b>TIRE SIZE</b>	<b>520/85 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE / VENDEMMIATRICE / MIETITREBBIA
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 A8/B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94044771	<b>RC (IN)</b>	220.2
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	72.8	<b>RIM ALT</b>	DW 18 L ; DD 16 L
<b>SLR (IN)</b>	32.7	<b>ECE</b>	E4-106R-001483

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	4710	5470	6240	7010	7780	8540
25	4710	5470	6240	7010	7780	8540
20	5040	5860	6680	7510	8330	9150
5 LT	6300	7330	8370	9390	10430	11450
5 HT	5040	5860	6680	7510	8330	9150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.