


# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>710/70 R 38</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SPRAYER / TRACTOR / VINEYARD<br>HARVESTER / HARVESTER /<br>IMPLEMENTS                    |
| <b>VERSION</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 175 D ; 178 A8   |



## DIMENSIONS US STANDARD

|                 |          |                 |                 |
|-----------------|----------|-----------------|-----------------|
| <b>USA CODE</b> | 94063536 | <b>RC (IN)</b>  | 226.4           |
| <b>SW (IN)</b>  | 28.2     | <b>RIM REC</b>  | DW 23 B         |
| <b>OD (IN)</b>  | 77.1     | <b>ECE</b>      | E11-106R-006000 |
| <b>SLR (IN)</b> | 33.8     | <b>TRA CODE</b> | R1W             |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15    | 17    | 20    | 23    | 29    | 35    | 41    | 47    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40        | 5940 | 7000 | 8070  | 8980  | 10040 | 10960 | 12030 | 12930 | 14150 | 15210 |
| 30        | 6240 | 7350 | 8470  | 9420  | 10550 | 11510 | 12620 | 13580 | 14860 | 15970 |
| 25        | 6450 | 7610 | 8760  | 9750  | 10910 | 11900 | 13060 | 14050 | 15380 | 16530 |
| 20        | 6820 | 8060 | 9280  | 10330 | 11550 | 12600 | 13820 | 14870 | 16270 | 17490 |
| 5 LT      | 7960 | 9380 | 10810 | 12040 | 13460 | 14680 | 16110 | 17340 | 18970 | 20390 |
| 5 HT      | 6820 | 8060 | 9280  | 10330 | 11550 | 12600 | 13820 | 14870 | 16270 | 17490 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.