

EARTHMAX SR 25 PLUS



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 25 PLUS

EARTHMAX SR 25 PLUS (G-2/L-2) is an All Steel radial tyre, which has been specially designed for motor graders and loaders operating in the most severe road construction or mining applications. Its non-directional tread design offers excellent self-cleaning properties in addition to traction and stability off the road.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø24"	14.00 R 24	TL	G2/L2	*	153 A8 175 A2	8.00TG	9.00GR	0	359	1372	626	4146	25	CR
	13.00 R 24	TL	G-2/L-2	*	146 A8 167 A2	8.00 TG	9.00 GR 10.00 VA	0	337	1290	588	3947	26	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES			PERFORMANCES		
					
	G-2/G2/L-2/L2				
					
A8	175 kg				

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKRishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026