


# MULTIMAX MP 522

<b>TIRE SIZE</b>	<b>280/80 R 18 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	KOMPAKTLADER / TELESKOPLADER / KOMPAKTLADER / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	132 A8/B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	282	<b>RIM REC</b>	W 9; 9; 9 SDC
<b>OD (MM)</b>	907	<b>RIM ALT</b>	W 8; W 10
<b>SLR (MM)</b>	421	<b>ECE</b>	E11-106R-002962
<b>RC (MM)</b>	2748	<b>SRI</b>	425

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	960	1140	1300	1480	1660	1780	2000	-	-
40	960	1140	1300	1480	1660	1780	2000	-	-
30	1030	1220	1395	1585	1780	1905	2140	-	-
25	1070	1270	1445	1645	1845	1980	2220	-	-
10 CYC.	1170	1440	1695	1950	2220	2415	2730	2880	3000
STATIC	1795	2210	2600	2990	3405	3705	4190	4420	4600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.