


# MULTIMAX MP 522

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>480/80 R 26 IND</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL               |
| <b>MACHINERY</b>    | CARREGADORA COMPACTA /<br>LEVANTADOR TELESCÓPICO /<br>CARREGADORA COMPACTA /<br>LEVANTADOR TELESCÓPICO |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 167 A8/B   |



## DIMENSÕES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94073108 | <b>RC (IN)</b> | 168.8           |
| <b>SW (IN)</b>    | 18.9     | <b>RIM REC</b> | DW 15 L         |
| <b>OD (IN)</b>    | 56.2     | <b>RIM ALT</b> | DW 16 L         |
| <b>SLR (IN)</b>   | 25.1     | <b>ECE</b>     | E11-106R-008146 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 23    | 26    | 29    | 32    | 35    | 38    | 41    | 44    | 46    | 49    | 52    | 55    | 58    | 61    | 64    |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| <b>30</b>     | 5680  | 6210  | 6730  | 7260  | 7800  | 8330  | 8860  | 9390  | 9920  | 10450 | 10970 | 11500 | 12010 | -     | -     |
| <b>25</b>     | 5680  | 6210  | 6730  | 7260  | 7800  | 8330  | 8860  | 9390  | 9920  | 10450 | 10970 | 11500 | 12010 | -     | -     |
| <b>20</b>     | 6150  | 6710  | 7270  | 7830  | 8390  | 8950  | 9510  | 10060 | 10630 | 11190 | 11750 | 12300 | 12860 | -     | -     |
| <b>15</b>     | 6370  | 6960  | 7540  | 8110  | 8700  | 9280  | 9870  | 10440 | 11020 | 11610 | 12180 | 12760 | 13340 | -     | -     |
| <b>5 CYC.</b> | 7050  | 7840  | 8620  | 9400  | 10180 | 10970 | 11750 | 12530 | 13320 | 14100 | 14880 | 16450 | 18020 | -     | -     |
| <b>STATIC</b> | 10800 | 12000 | 13200 | 14410 | 15610 | 16810 | 18010 | 19210 | 20410 | 21620 | 22820 | 24020 | 25230 | 26430 | 27630 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.