


AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 24X8.50 - 12 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 81 A8 |
| LI/SS FREE ROLLING | 94 A8 |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|------------------|
| CODICE USA | 94512409 | RC (IN) | 69.3 |
| SW (IN) | 8.5 | RIM REC | 7 JA; 7.00 I |
| OD (IN) | 24.0 | ECE | E11-106R-0010452 |
| SLR (IN) | 11.2 | PR | 6 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 74 |
|-----------|------|
| 5 FR | 2070 |
| 15 FR | 1750 |
| 20 FR | 1650 |
| 25 FR | 1480 |
| 5 DW | 1420 |
| 15 DW | 1215 |
| 20 DW | 1140 |
| 25 DW | 1020 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.