

# EM 936

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 17.5 - 25                                 |
| <b>UM</b>           | IS STANDARD                               |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                    |
| <b>MACHINERY</b>    | PALA EXCAVADORA / ELEVADOR<br>TELESCÓPICO |
| <b>VERSIÓN</b>      | DUAL BEAD                                 |
| <b>TIRE TYPE</b>    | TL  |



## DIMENSIONES IS STANDARD

|                 |           |                 |       |
|-----------------|-----------|-----------------|-------|
| <b>OD (MM)</b>  | 1340      | <b>PR</b>       | 24    |
| <b>SLR (MM)</b> | 600       | <b>TRA CODE</b> | E2/L2 |
| <b>RC (MM)</b>  | 4060      |                 |       |
| <b>RIM REC</b>  | 14.00/1.5 |                 |       |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>7.00</b> |
| 10                | 10000       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.