


AGRIMAX PROHARVEST

TIRE SIZE	VF 800/65 R 32 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	187 D



DIMENSIONER IS STANDARD

SW (MM)	786	RIM REC	DW 28 B
OD (MM)	1853	RIM ALT	DW27B; DW30B
SLR (MM)	818	ECE	E11-106R-0011693
RC (MM)	5562	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8
70	2545	2960	3375	3790	4145	4500	5030	5385	5915
FROM 65 TO 40	4195	4875	5560	6240	6825	7410	8290	8875	9750
30	4280	4975	5670	6365	6965	7560	8455	9050	9945
20	4365	5070	5780	6490	7100	7710	8620	9230	10140
10	4615	5365	6115	6865	7510	8155	9120	9760	10725
*UPTO 30 CYC	4765	5535	6310	7085	7750	8415	9410	10075	11070
*UPTO 15 CYC	5685	6610	7535	8460	9255	10045	11235	12030	13215
*UPTO 10 CYC	6230	7240	8255	9270	10140	11005	12310	13180	14480
10HT	4280	4975	5670	6365	6965	7560	8455	9050	9945

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.